

DUAL CAMERA & LED LIGHT CONTROLLER

This dual controller provides power and control for two underwater video cameras and lights in a rugged, lightweight and easy to operate package.

Housed in an attractive power coated, extruded Aluminium case with clearly marked controls, it is ideal for use in dive control rooms or mobile units where space is at a premium.

This unit is compatible with all Submertec composite video cameras, such as the DHC5 and LED video lights such as the UVL3.

Cameras and lights are individually switched.

Brightness controls provide dimming of the lights.

Lights are powered from variable constant current outputs at up to 2 Amps for use with Submertec UVL3 lights.

Controls on the rear panel allow the maximum current to be limited if required for operation with different lights.



All connections are to the rear panel which is clearly marked.

Two independent BNC video outputs are provided from each camera to allow additional monitors to be connected.

The video level from each camera can be adjusted if required.



Submertec Dual Camera and LED Light Controller	
Dimensions	233mm wide, 140mm high, 315mm deep (excl handles).
Weight	3.65 Kg
Power Source	100-240 vac 50 / 60 Hz
Camera power	15v
Lamp Power	Constant current from 28v source.
Lamp Control	Variable current at up to 2 Amps.
Video input	CVBS (Composite)
Video Output	Adjustable level with 2 independent buffered outputs
Umbilical connection options	Amphenol 97-3106-18-1P (on cable end) Or Amphenol CA-3106E18-1PB (on cable end)

Also available as a triple Camera / Light version

Seaspy underwater video equipment is available in a number of configurations and with control options to suit a range of tasks from inspection to aquaculture – please visit our web site at www.submertec.co.uk to view these together with other Submertec products.